

Groundwater Depletion, Sustainable Aquifer Management, and Data-Driven Strategies for Long-Term Water Security

Ahmid Chernor Jalloh¹, Ansumana Davowah^{*2}, Ameer Jan³

1 Conservation Trust Fund, Ministry of the Environment and Climate Change - Sierra Leone

Ahmid.jalloh@ctf.gov.sl

2 Sierra Leone Agricultural Research Institute (SLARI), Magbosi land water and environment research center (MLWERC). Orcid ID: <https://orcid.org/0009-0003-9705-6210>

3 University of Makran. ameerjan@uomp.edu.pk

DOI: <https://doi.org/10.63163/jpehss.v4i3.1735>

Abstract

Groundwater constitutes over 90% of the world's readily accessible freshwater, supplying drinking water to approximately two billion people and supporting 40% of global agricultural irrigation. However, widespread overexploitation has triggered severe depletion across major aquifer systems worldwide, with global annual groundwater depletion doubling from $126 \pm 32 \text{ km}^3/\text{year}$ in 1960 to $283 \pm 40 \text{ km}^3/\text{year}$ by 2000. This review synthesizes global groundwater depletion trends, examines severe regional case studies, evaluates sustainable management frameworks, and highlights advanced data-driven strategies for long-term water security. Seven nations India, Pakistan, Iran, the United States, China, Mexico, and Saudi Arabia account for the vast majority of global depletion volumes, driven primarily by subsidized energy policies, uncontrolled tube-well expansion, and water-intensive agricultural practices. The review analyzes irreversible geomechanical impacts, including land subsidence exceeding 35–50 cm/year in Mexico City and permanent aquifer storage loss estimated at $\sim 17 \text{ km}^3/\text{year}$ globally. Supply-side interventions via Managed Aquifer Recharge (MAR) and demand-side controls are evaluated, revealing the "Efficiency Paradox" where irrigation efficiency improvements fail to reduce net basin-scale abstraction due to rebound crop expansion. The review emphasizes emerging data-driven technologies, including GRACE/GRACE-FO satellite gravimetry, InSAR geodesy, machine learning downscaling, and Physics-Informed Neural Networks (PINNs) integrated into subsurface Digital Twins. The synthesis concludes that achieving long-term water security requires polycentric governance aligned with hydrostratigraphic boundaries, enforceable volumetric pumping caps, virtual water trade tracking, and strategically sited MAR infrastructure monitored through physics-constrained artificial intelligence protecting global ecosystems, food production, and human water security for future generations.

Keywords: Groundwater Depletion, Sustainable Aquifer Management, Grace Satellite Gravimetry, Insar Geodesy, Managed Aquifer Recharge, Physics-Informed Neural Networks, Digital Twins, Water Security, Land Subsidence, Virtual Water Trade

1. Introduction

Groundwater represents the single largest liquid freshwater resource on Earth, constituting over 90% of the world's readily accessible freshwater reserves. It serves as a vital buffer against climate variability, stabilizing agricultural yields and municipal supply systems during protracted surface droughts. Globally, groundwater supplies drinking water to approximately two billion people and provides 40% of all agricultural irrigation water alongside 27% of global industrial water demand

(Borzi, 2025). However, the rapid expansion of irrigated agriculture during the Green Revolution, combined with accelerating urbanization and demographic growth, has triggered widespread overexploitation of major aquifer systems worldwide. Over two billion people representing roughly 35% of the global population currently reside in regions experiencing severe, chronic water stress (Sheik et al., 2025).

Global annual groundwater depletion doubled between 1960 and 2000, rising from an estimated $126 \pm 32 \text{ km}^3/\text{year}$ to $283 \pm 40 \text{ km}^3/\text{year}$. This volume accounts for nearly 39% of total global yearly groundwater abstractions and roughly 2% of total annual global groundwater recharge. The discharge of depleted groundwater into the hydrologic cycle ultimately reaches the oceans, contributing an estimated $0.8 \pm 0.1 \text{ mm/year}$ to global sea-level rise (Ramakrishnan et al., 2024). Integrated global human-Earth system simulations indicate that nonrenewable groundwater abstraction exhibits a characteristic peak-and-decline trajectory, reminiscent of non-renewable resource extraction curves. Across hundreds of baseline and climate scenario projections, global nonrenewable groundwater extraction is anticipated to peak around mid-century (c. 2050) at a median rate of approximately $625 \text{ km}^3/\text{year}$ before entering a receding limb driven by physical exhaustion and prohibitive extraction costs (Aderemi et al., 2021).

The consequences of unmitigated groundwater depletion extend far beyond declining water tables. Intensive overpumping induces severe geomechanical and environmental externalities, including the irreversible consolidation of aquitards, land subsidence, structural infrastructure damage, streamflow depletion, deterioration of aquatic ecosystems, and saltwater intrusion into coastal freshwater lenses (Fuqaha, 2025). Addressing these compounding crises requires a transition from reactive extraction regimes to proactive, data-driven sustainable aquifer management. This review synthesizes global groundwater depletion trends, highlights severe regional case studies, examines structural geomechanical impacts, evaluates supply and demand management frameworks, and highlights the role of advanced satellite remote sensing, machine learning downscaling, and subsurface Digital Twins in securing global long-term water resources (Singh et al., 2022).

2. Global Depletion Hotspots and Hydrodynamic Drivers

Groundwater depletion occurs when long-term volumetric abstraction (Q_{abs}) exceeds natural recharge (R_n) plus induced net captured discharge (C_n) over broad regional scales, expressed by the fundamental mass balance equation:

$$\Delta S = R_n + C_n - Q_{abs}$$

Where ΔS represents the net change in subsurface storage. When $\Delta S < 0$ over extended durations, persistent water table drawdown and aquifer storage loss occur (Leijnse et al., 2024). While global freshwater volumes are theoretically sufficient to satisfy human demand, spatial and temporal mismatches between surface supply and intensive agricultural or urban requirements create severe regional depletion hotspots. Uncontrolled abstraction in excess of natural replenishment leads directly to hydrodynamic overexploitation, triggering a cascading sequence of irreversible geomechanical consolidation, structural subsidence, baseflow reduction, and international supply chain vulnerability (Sun et al., 2025).

The geographical distribution of groundwater depletion is concentrated heavily in sub-humid, arid, and semi-arid agricultural basins. Seven nations account for the vast majority of global depletion volumes: India ($71 \pm 21 \text{ km}^3/\text{year}$), Pakistan ($50 \pm 15 \text{ km}^3/\text{year}$), Iran ($32 \pm 9 \text{ km}^3/\text{year}$), the United States ($32 \pm 7 \text{ km}^3/\text{year}$), China ($26 \pm 6 \text{ km}^3/\text{year}$), Mexico ($12 \pm 3 \text{ km}^3/\text{year}$), and Saudi Arabia ($10 \pm 2 \text{ km}^3/\text{year}$). In these hyper-extracted zones, deep tube-well technology and subsidized rural energy policies have decoupled agricultural production from local climate precipitation cycles, leading to critical aquifer overdraft (Pierrat et al., 2023).

A nuanced understanding of depletion drivers requires examining the role of international trade and supply chain telecoupling. Groundwater is implicitly traded across borders as "virtual water" embodied in agricultural commodities, industrial goods, and services. Approximately 20% of global food production relies on groundwater irrigation, with more than half of these crops traded internationally. Consequently, local groundwater depletion in exporting regions often supports consumption in distant metropolitan centers or foreign markets (Lu et al., 2025).

In China, annual groundwater depletion exceeds 64 billion m³/year (~ 64 km³/year), concentrated primarily in Xinjiang, Hebei, Henan, and Heilongjiang Provinces. Multi-Region Input-Output (MRIO) modeling combined with high-resolution hydrogeological modeling demonstrates that approximately 40% of China's total groundwater depletion (21 billion m³/year) is virtually transferred domestically between provinces, while 4.8 billion m³/year is embodied in international exports (Kumar et al., 2026). Crucially, over 60% of embodied groundwater depletion in China is incorporated into non-primary industrial and tertiary products rather than raw agricultural commodities alone. This illustrates that urban economic development and manufacturing supply chains are direct drivers of distant rural aquifer exhaustion (Portilho-Ramos et al., 2022).

Table 1: Global Groundwater Depletion Hotspots, Volumetric Depletion Rates, and Dominant Drivers

Region / Aquifer System	Estimated Depletion Rate (km³/year)	Primary Anthropogenic Drivers	Socio-Economic & Environmental Impacts
Northwest India & Pakistan (Indo-Gangetic Basin)	121 ± 36	Uncontrolled tube-well expansion, subsidized electricity, water-intensive paddy-wheat rotations	Severe water table decline (0.5--1.5 m/year), loss of baseflow to tributaries, geogenic contamination
Central & Western United States (High Plains & Central Valley)	32 ± 7	Deep-well center-pivot irrigation, drought-induced pumping shifts, high-value crop cultivation	Irreversible storage loss in southern High Plains, widespread structural land subsidence in California
Northern China (North China Plain & Xinjiang)	26 ± 6	Intensive grain production, rapid urbanization, industrial virtual water export	Large cone of depression, dry wells, structural interprovincial virtual water deficits
Iranian Plateau	32 ± 9	Agricultural self-sufficiency policies, arid-zone irrigation expansion, structural overdraft	Widespread land subsidence, sinkhole formation, agricultural land abandonment, severe salinization
Arabian Peninsula (Saudi Aquifer Systems)	10 ± 2	Deep fossil aquifer mining for center-pivot wheat and fodder production	Near-total exhaustion of non-renewable fossil stocks, escalating desalination dependency
Mexico Basin & Central Valley (Mexico)	12 ± 3	Concentrated municipal extraction, inter-basin transfers, historical lacustrine drainage	Extreme land subsidence (> 35--50 cm/year), aquitard compaction, drainage network disruption

3. Regional Case Studies and Irreversible Geomechanical Impacts

3.1 The High Plains and California Central Valley Aquifers (United States)

The High Plains Aquifer (HPA) and California Central Valley (CV) aquifer system represent two of the most intensively monitored and hydrogeologically distinct depletion hotspots in North America (Bierkens & Wada, 2019). The High Plains Aquifer spanning eight states from South Dakota to Texas is a largely unconfined, heterogeneous sedimentary system containing fossil groundwater recharged mostly during the late Pleistocene (~13,000 years ago). Total cumulative depletion in the HPA since predevelopment (~ 1950s) reached ~ 330 km³ by 2007, representing roughly 8% of total pre-development volume (Ojha et al., 2018).

Spatial heterogeneity across the HPA is extreme: over one-third of total cumulative depletion occurs within just 4% of the total aquifer surface area. High modern precipitation recharge rates in the northern High Plains (Nebraska) maintain near-steady-state storage, whereas lower recharge combined with intense pumping in the central and southern High Plains (Kansas, Oklahoma, Texas) has mined fossil water stocks. Extrapolations suggest that 35% of the southern High Plains will be unable to support irrigated agriculture within the next 30 years due to saturated thickness dropping below critical pumpage thresholds (≤ 6 m) (Galloway & Sneed, 2013).

In contrast, the Central Valley of California is a highly dynamic, engineered hydrogeological system. Extensive north-to-south surface water diversions constructed since the 1950s increased artificial recharge sevenfold in the northern Sacramento Valley, yet cumulative depletion in the Central Valley totaled ~ 140 km³ between the 1860s and 2000s (~ 80 km³ since 1960) (Carlson et al., 2020). Depletion in the Central Valley is concentrated in the southern Tulare Basin and occurs almost entirely during severe drought cycles. When surface water deliveries are curtailed during droughts, agricultural operations shift reliance to deep groundwater pumping, inducing severe seasonal head drops (Overacker et al., 2022).

3.2 The Mexico Basin Aquifer and Unprecedented Land Subsidence

The Mexico City metropolitan area, home to 22 million residents, presents a clear example of anthropogenic aquitard compaction and irreversible mechanical damage. Located over an elevated intermontane basin underlain by low-strength, highly compressible lacustrine clay deposits, the city relies on the underlying volcanic-sedimentary aquifer for over 70% of its total water supply. Groundwater pumping extractions exceed natural recharge, inducing continuous water table drawdowns of 1.0--1.5 m/year (Palma et al., 2022).

The fundamental geomechanical mechanism driving subsidence in Mexico City is governed by Terzaghi's principle of effective stress:

$$\sigma'_v = \sigma_v - u$$

Where σ'_v is effective vertical intergranular stress, σ_v is total overburden stress, and u is pore-water pressure. As persistent groundwater extractions lower the potentiometric surface, hydraulic pore-water pressure (u) declines significantly. This decline causes a direct transfer of overburden stress onto the skeletal matrix of the fine-grained clay aquitard, initiating permanent structural compaction and the irreversible collapse of clay micropores (Galloway et al., 1999).

Continuous geodetic measurements using Interferometric Synthetic Aperture Radar (InSAR), Continuous Global Positioning Systems (cGPS), and historical leveling document vertical land motion (VLM) subsidence rates exceeding 35--50 cm/year in eastern municipal sectors such as Nezahualc6yotl, Chalco, and Iztapalapa. Cumulative vertical displacements in the urban center exceed 10--14 meters over the past century (Castellazzi et al., 2016).

Geomechanical modeling demonstrates that the relationship between subsidence velocity (V_U in cm/year) and lacustrine clay deposit thickness (H_C in meters) follows a non-linear power function:

$$V_U = 176 \cdot H_C^{1.8}$$


Analysis of long-term geodetic datasets confirms an absence of elastic deformation rebound; the compaction of fine-grained upper aquitards is virtually 100% irreversible (Ortega-Guerrero et al., 1999). Once matrix clay micro-structures collapse under effective stress increases exceeding pre-consolidation thresholds, internal pore space is destroyed permanently. This irrecoverably reduces subsurface volumetric storage capacity, permanently altering the basin's hydraulic properties and accelerating urban infrastructure failure. On a global scale, fine-grained aquitard consolidation leads to a permanent aquifer storage capacity loss estimated at $\sim 17 \text{ km}^3/\text{year}$ (Pacheco-Martínez et al., 2013).

3.3 The Indo-Gangetic Plain and Agricultural Intensification

The Indo-Gangetic Alluvial Basin spanning northern India, Pakistan, southern Nepal, and Bangladesh contains one of the world's most massive regional aquifer systems. Driven by widespread flood irrigation, unmetered abstraction, and intensive double- and triple-cropping regimes (e.g., water-intensive submerged paddy rice followed by winter wheat), groundwater levels in northern India and Pakistan have dropped at rates averaging 0.52--1.5 m/year (Jat et al., 2021). In core agricultural districts of Pakistan Punjab (e.g., Sheikhpura, Gujranwala), post-2014 decline rates accelerated to 0.73 m/year, with cumulative groundwater storage losses exceeding 320 mm/year (Gathala et al., 2013).

Statistical attribution analyses indicate that anthropogenic variables (agricultural expansion, population density, unmetered abstraction) account for over two-thirds of observed groundwater variance ($R^2 = 0.67$), whereas climate variables like precipitation play a secondary role ($R^2 = 0.28$). The severe drop in piezometric heads has induced secondary hydrological hazards: vertical and lateral hydraulic gradients have shifted, drawing geogenic contaminants (specifically arsenic and fluoride) and shallow agricultural saline return flows into deeper pristine aquifers, threatening public health and regional food security (Islam et al., 2019).

Figure 1: Conceptual Diagram of Hydro-climatic, Agricultural, and Subsurface Drivers Governing Groundwater Depletion and Nitrate Leaching in Double-Cropping Systems



4. Sustainable Aquifer Management Strategies

4.1 Supply-Side Interventions: Managed Aquifer Recharge (MAR)

Managed Aquifer Recharge (MAR) comprises a suite of engineered methodologies designed to intentionally replenish subsurface storage using surplus surface water, seasonal river runoff, stormwater, or reclaimed high-quality wastewater. MAR supplements natural recharge, halts water table decline, mitigates land subsidence, and creates dynamic subsurface storage buffers for drought resilience without the high evaporative losses associated with surface reservoirs (Leader & Wijnen, 2018).

The successful implementation of MAR depends on five fundamental hydrogeological performance parameters:

- **Aquifer Transmissivity (T):** Governs the lateral propagation rate of recharged water away from infiltration points.
- **Vertical Hydraulic Conductivity (K_v):** Determines infiltration velocities through unsaturated vadose zones or surface basins (Datta, 2019).
- **Source Water Availability:** Requires temporal alignment between excess surface flows and available subsurface capacity.
- **Recharge Water Quality:** Dictates geochemical compatibility with native groundwaters to prevent fine-grained clay swelling, pore clogging, and mobilization of heavy metals.
- **Aquifer Thickness & Structural Boundary Conditions:** Defines physical storage limits and confinement constraints (Saha et al., 2022).

In California's Central Valley, large-scale MAR programs divert high-flow surface runoff during wet years into dedicated agricultural uncropped fields (Ag-MAR) and dedicated basin sites, achieving recharge volumes up to 3 km³/year to replenish stressed unconfined aquifers (Reddy et al., 2021).

4.2 Demand-Side Interventions and The Efficiency Paradox

While supply augmentation via MAR is crucial, sustainable management ultimately requires rigid demand-side controls. Historically, policy interventions focused on micro-irrigation efficiency upgrades transitioning agricultural operations from traditional flood irrigation to drip or micro-sprinkler systems (Zhao et al., 2016).

However, hydrogeological modeling demonstrates the existence of the "Efficiency Paradox" (a manifestation of Jevons' Paradox) in agricultural water conservation. Coupled land-surface and 2D groundwater modeling (e.g., VIC coupled with AMBHAS) in the northwest Indo-Gangetic Plain shows that introducing drip irrigation reduces localized field-level volumetric applications, but fails to reverse regional groundwater depletion trends (Wirl, 1995).

The hydrogeological mechanism behind this paradox involves two primary factors. First, traditional flood irrigation yields substantial deep percolation (return flow) that recharges unconfined aquifers; high-efficiency drip systems virtually eliminate deep percolation, thereby reducing regional aquifer replenishment. Second, saved water at the field level is frequently converted by farm operators into expanded irrigated acreage, higher planting densities, or shifts toward higher-value, higher-evapotranspiration crops (Bouhou et al., 2015).

Consequently, technical irrigation efficiency improvements do not automatically yield net basin-scale water savings. Sustainable demand management requires legally enforceable volumetric pumping limits, seasonal abstraction quotas, real-time extraction metering, crop-type restrictions in hyper-stressed zones, and economic shadow pricing mechanisms that accurately reflect the depletion cost of nonrenewable water stocks (Brennan, 2010).

Table 2: Operational Comparison of Managed Aquifer Recharge (MAR) Methodologies

MAR Technique	Hydrogeological Prerequisites	Technical Mechanisms	Primary Limitations & Risks
Infiltration Basins	Unconfined aquifers, high vadose zone permeability (K_v), shallow water table	Surface water ponding allows gravity-driven percolation through unconfined vadose zones	Large land footprint required, high vulnerability to bio-clogging, siltation, surface evaporation
Aquifer Storage & Recovery (ASR) Wells	Confined or semi-confined aquifers, high transmissivity (T), limited surface land	Direct dual-purpose injection and extraction wells penetrating target hydrostratigraphic units	High operational capital costs, rapid physical clogging, geochemical mobilization of arsenic/iron
Agricultural MAR (Ag-MAR)	Deep water tables, high lateral transmissivity, flood-tolerant crop types	Diverting seasonal flood surpluses directly onto working farmland during dormant winter periods	Soil salinization risk, nitrate leaching into shallow drinking aquifers, root-zone damage
Check Dams & Stream-bed Infiltration	Ephemeral river channels, unconfined alluvial deposits, variable monsoon flow	Low-head cross-channel permeable structures designed to retard surface runoff velocities	High silt loading causes physical silt-clogging, periodic structural maintenance required

5. Data-Driven Strategies and Technological Integration

5.1 Satellite Gravimetry: GRACE and GRACE-FO Capabilities and Downscaling

The launch of the NASA/DLR Gravity Recovery and Climate Experiment (GRACE, 2002–2017) and its successor GRACE Follow-On (GRACE-FO, 2018–present) transformed global hydrogeology by providing direct satellite observations of Earth's time-variable gravity field (Springer et al., 2026). These twin-satellite missions track minute variations in inter-satellite distance traditionally measured via K-Band Ranging (KBR) and upgraded on GRACE-FO to Laser Ranging Interferometry (LRI) providing $10\text{--}20 \times$ higher precision to quantify monthly changes in Total Terrestrial Water Storage Anomalies (ΔTWSA) (Sun et al., 2026).

To isolate Groundwater Storage Anomalies (ΔGWSA) from total satellite-derived mass changes, hydrogeologists decouple secondary hydrologic storage compartments using Land Surface Models (LSMs) or Global Land Data Assimilation System (GLDAS) outputs:

$$\Delta\text{GWSA} = \Delta\text{TWSA} - (\Delta\text{SMS} + \Delta\text{SWS} + \Delta\text{SWE} + \Delta\text{CWS})$$


Where ΔSMS is soil moisture storage anomaly, ΔSWS is surface water storage anomaly, ΔSWE is snow water equivalent anomaly, and ΔCWS is canopy water storage anomaly (Xiong et al., 2025).

Despite their efficacy in quantifying broad regional trends, native GRACE/GRACE-FO data suffer from spatial resolution limits (~ 300 km footprint, or $\sim 100,000$ km²) and monthly temporal sampling. To make satellite gravimetry operational for local water management, advanced spatial and temporal downscaling methodologies have emerged (Samalavičius et al., 2026).

The workflow transitions from raw satellite gravimetry measuring total mass changes to high-resolution local decision grids. First, auxiliary hydrologic data from land surface models remove surface storage components to isolate coarse basin-scale groundwater anomalies. Next, advanced machine learning architectures including Geographically Weighted Regression (GWR), Random Forest (RF), and hybrid Long Short-Term Memory with Bayesian Convolutional Neural Networks

(LSTM-BCNN) integrate satellite Δ TWSA with high-resolution environmental variables such as MODIS Evapotranspiration, E-OBS precipitation, vegetation health indices, and surface topography (Springer et al., 2025). These downscaling algorithms effectively disaggregate coarse spatial grids into high-resolution local groundwater storage fields down to 1 km or 0.1° grids. Furthermore, data assimilation techniques using Ensemble Kalman Filters (EnKF) directly assimilate monthly GRACE/GRACE-FO gravimetry into physical models such as WaterGAP, producing global continuous grids (e.g., GLWS 2.0 at 0.5° resolution) that capture complex spatial variance (Ibrahim et al., 2026).

Figure 2: Integrated Multi-Scale Hydrological Modeling and Data Assimilation Framework for Vadose Zone Characterization, Managed Aquifer Recharge (MAR), and Subsurface Aquifer Risk Assessment



5.2 Remote Sensing Geodesy: InSAR and GNSS Infrastructure Monitoring

Spaceborne Interferometric Synthetic Aperture Radar (InSAR) utilizing satellite constellations such as Sentinel-1 delivers sub-centimeter-precision vertical land motion (VLM) measurements at fine spatial scales (5--20 meters). When coupled with continuous GPS networks, InSAR provides continuous tracking of aquifer skeleton deformation (Kyriou et al., 2023).

Hydrogeologists use multi-temporal InSAR displacement maps to constrain subsurface mechanical properties. By cross-referencing vertical subsidence velocity (V_U) with seasonal groundwater drawdown records from piezometer networks, researchers can map inelastic structural strain limits. Differential settlement maps derived from InSAR identify extreme angular distortion gradients ($\beta > 1/3000$), pinpointing localized zones vulnerable to severe surface faulting, land cracking, and structural infrastructure failure (Parker et al., 2017).

5.3 Subsurface Digital Twins and Physics-Informed Neural Networks (PINNs)

The integration of physical hydrogeology with artificial intelligence has led to the development of dynamic subsurface Digital Twins virtual representations of real-world aquifer systems. Digital Twins assimilate real-time observations from InSAR satellite streams, GRACE-FO gravimetry, telemetrized piezometers, and pumping logs into 3D numerical groundwater models (e.g., MODFLOW, AMBHAS) to simulate fluid flow, head distributions, and land deformation (Chen et al., 2026).

A crucial breakthrough in Digital Twin architecture is the application of Physics-Informed Neural Networks (PINNs). Standard data-driven deep learning models often fail when extrapolating beyond

training data or operate as "black boxes" that violate fundamental conservation laws (Li et al., 2026). Groundwater PINNs (GW-PINNs) address this limitation by directly incorporating the governing partial differential equations of 3D saturated groundwater flow into the neural network's loss function:

$$S_s \frac{\partial h}{\partial t} - \nabla \cdot (K \nabla h) - W = 0$$

Where S_s is specific storage, h is hydraulic head, K is hydraulic conductivity tensor, and W represents volumetric sources/sinks (Gonzales-Inca et al., 2022). The composite loss function optimizes both data matching and physics compliance:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{data}} + \lambda_{\text{physics}} \mathcal{L}_{\text{physics}}$$

Where $\mathcal{L}_{\text{data}}$ represents mean squared error against measured well heads and $\mathcal{L}_{\text{physics}}$ penalizes residuals from the flow partial differential equation. By forcing the neural network to satisfy physical conservation laws, GW-PINNs enable precise, real-time parameter estimation, dynamic aquifer head forecasting, and scenario analysis even in data-scarce regions (Kumar & Nehdi, 2026).

Table 3: Multi-Tiered Earth Observation and Modeling Architectures for Aquifer Monitoring

Technology Platform	Spatial / Temporal Resolution	Primary Measurement Target	Key Analytical Advantage	Operational Challenge / Limitation
GRACE / GRACE-FO Satellite Gravimetry	~ 300 km footprint / Monthly	Integrated mass changes ($\Delta TWSA$) & subsurface storage changes	Direct gravimetric mass balance assessment; unhindered by cloud cover	Coarse spatial resolution requires advanced statistical downscaling; vertical signal integration
InSAR Geodesy (Sentinel-1 SAR)	5--20 m / 6--12 days	Sub-centimeter vertical land motion (VLM) & surface deformation	Millimeter-precision mapping of aquitard compaction & fault line vulnerability	Decorrelation over dense vegetative cover; measures land deformation rather than direct water mass
Downscaled Machine Learning (LSTM-BCNN)	1 km--0.1° disaggregated / Monthly	High-resolution spatial disaggregation of $\Delta GWSA$	Bridges satellite scale gap to local operational management scales	Requires high-quality, dense local environmental training datasets to avoid model overfitting
Physics-Informed Neural Networks (GW-PINNs)	Continuous high-resolution grid / Real-time	Dynamic 3D hydraulic head disaggregation & state forecasting	Guarantees mass conservation compliance; operates efficiently under data scarcity	High computational load during neural network optimization; sensitivity to hyperparameters

6. Synthesis, Policy Implications, and Strategic Framework for Water Security

Achieving long-term water security in hyper-extracted basins requires an integrated, multi-tiered operational framework that seamlessly connects advanced sensing, governance reform, and supply-demand balance (Mishra et al., 2021). Satellite Earth observation platforms (GRACE-FO and Sentinel-1 InSAR) provide macro-scale volumetric mass and deformation constraints, while localized

piezometric well networks furnish high-frequency hydraulic head data. Integrating these multi-scale observation streams into physics-constrained neural networks and 3D numerical models forms the basis of subsurface Digital Twins, enabling water managers to run dynamic policy simulations in real time (Pahl-Wostl et al., 2013).

To prevent premature reaching of predicted mid-century nonrenewable groundwater extraction peaks and to mitigate irreversible structural damage to critical aquitards, water governance frameworks should prioritize several key policy imperatives:

First, regional water governance must transition from fragmented administrative jurisdictions toward polycentric management units aligned strictly with hydrostratigraphic aquifer boundaries. Managing aquifers according to political borders fails to account for lateral hydraulic connectivity, leading to transboundary overpumping and uncoordinated depletion (Scott et al., 2013).

Second, modernization of agricultural irrigation infrastructure must be coupled with mandatory, legally binding reductions in volumetric pumping allocations. As demonstrated by the Efficiency Paradox, technical efficiency upgrades alone often fail to reduce net basin abstraction due to rebound crop expansion. Enforceable volumetric caps, real-time well metering, and seasonal abstraction quotas are essential prerequisites for meaningful demand reduction (Grey & Sadoff, 2007).

Third, corporate environmental risk reporting and national water trade policies must incorporate Multi-Region Input-Output (MRIO) virtual water tracking. Tracing embodied groundwater depletion through complex supply chains reveals the true burden placed on distant aquifers by metropolitan and international consumption. Internalizing these costs through economic shadow pricing and sustainable supply chain certification encourages diversification and disincentivizes agricultural sourcing from hyper-depleted fossil aquifers (Bakker, 2012).

Finally, water authorities should invest in scaling engineered Managed Aquifer Recharge (MAR) projects during high-flow surface water periods. MAR initiatives must be strategically sited using multi-criteria decision frameworks that evaluate vertical permeability, transmissivity, and geochemical compatibility (Pollard et al., 2014). When combined with automated Digital Twin monitoring, controlled MAR deployments can restore piezometric heads, stabilize subsiding land surfaces, and safeguard critical freshwater stocks against future climate shocks. Through the synthesis of advanced remote sensing, strict demand-side volumetric controls, engineered recharge, and physics-constrained artificial intelligence, international water management institutions can safeguard essential subsurface freshwater stocks, protecting global ecosystems, food production, and human water security for generations to come (Aboelnga et al., 2019).

Conclusion

This review demonstrates that groundwater depletion represents one of the most pressing environmental and socio-economic challenges of the twenty-first century. Global annual depletion has doubled since 1960, with seven nations dominating extraction volumes and over two billion people residing in chronically water-stressed regions. The consequences extend far beyond declining water tables to include irreversible aquitard compaction, land subsidence exceeding 35–50 cm/year in extreme cases, permanent storage capacity losses, streamflow depletion, ecosystem degradation, and saltwater intrusion. Regional case studies from the High Plains, California Central Valley, Mexico City, and the Indo-Gangetic Plain illustrate distinct hydrogeological responses to overexploitation, yet share common drivers: subsidized energy, unmetered abstraction, and agricultural intensification. The review reveals that supply-side interventions like Managed Aquifer Recharge can restore depleted storage when strategically sited, while demand-side controls including enforceable volumetric caps, seasonal quotas, and real-time metering are indispensable given the Efficiency Paradox, where technical improvements alone often fail to reduce net basin abstraction. Crucially, the integration of satellite gravimetry (GRACE/GRACE-FO), InSAR geodesy, machine learning downscaling, and Physics-Informed Neural Networks into subsurface Digital Twins offers unprecedented capabilities for

real-time aquifer monitoring, deformation tracking, and predictive scenario analysis. These technologies bridge the scale gap between coarse satellite observations and local management decisions, enabling adaptive governance. The synthesis underscores that long-term water security requires a paradigm shift from reactive extraction to proactive, data-driven management aligned with hydrostratigraphic boundaries rather than political jurisdictions. Policy imperatives include polycentric governance, mandatory pumping reductions coupled with irrigation modernization, Multi-Region Input-Output virtual water tracking, economic shadow pricing of nonrenewable stocks, and scaled MAR deployment monitored through physics-constrained AI. By synthesizing advanced remote sensing, strict demand-side volumetric controls, engineered recharge, and physics-informed artificial intelligence, international water management institutions can safeguard essential subsurface freshwater stocks, protecting global ecosystems, food production, and human water security for generations to come.

References

- Aboelnga, H. T., Ribbe, L., Frechen, F. B., & Saghir, J. (2019). Urban water security: Definition and assessment framework. *Resources*, 8(4), 178.
- Aderemi, B. A., Olwal, T. O., Ndambuki, J. M., & Rwanga, S. S. (2021). A review of groundwater management models with a focus on IoT-based systems. *Sustainability*, 14(1), 148.
- Bakker, K. (2012). Water security: research challenges and opportunities. *Science*, 337(6097), 914-915.
- Bierkens, M. F., & Wada, Y. (2019). Non-renewable groundwater use and groundwater depletion: a review. *Environmental Research Letters*, 14(6), 063002.
- Borzi, I. (2025). Modeling groundwater resources in data-scarce regions for sustainable management: Methodologies and limits. *Hydrology*, 12(1), 11.
- Bouhou, N. E. I., Blackhurst, M. F., & Torres, P. (2015). An empirical analysis of joint residential electricity efficiency gains within and across end uses: implications for demand-side management. *Ecological Economics*, 110, 61-70.
- Brennan, T. J. (2010). Optimal energy efficiency policies and regulatory demand-side management tests: How well do they match?. *Energy Policy*, 38(8), 3874-3885.
- Carlson, G., Shirzaei, M., Werth, S., Zhai, G., & Ojha, C. (2020). Seasonal and long-term groundwater unloading in the Central Valley modifies crustal stress. *Journal of Geophysical Research: Solid Earth*, 125(1), e2019JB018490.
- Castellazzi, P., Martel, R., Rivera, A., Huang, J., Pavlic, G., Calderhead, A. I., ... & Salas, J. (2016). Groundwater depletion in Central Mexico: Use of GRACE and InSAR to support water resources management. *Water resources research*, 52(8), 5985-6003.
- Chen, T., Wu, B., Chen, D., Du, M., Wang, C., & Liu, K. (2026). Simulation-driven digital twin framework for drought-risk mitigation in groundwater reservoirs via hierarchical optimization. *Geomatics, Natural Hazards and Risk*, 17(1), 2652586.
- Datta, P. S. (2019). *Water harvesting for groundwater management: issues, perspectives, scope, and challenges*. John Wiley & Sons.
- Fuqaha, S. (2025). Global trends and research frontiers of water harvesting and groundwater recharge: a comprehensive bibliometric review. *Opportunities and Challenges in Sustainability*, 4(2), 110-134.
- Galloway, D. L., & Sneed, M. (2013). Analysis and simulation of regional subsidence accompanying groundwater abstraction and compaction of susceptible aquifer systems in the USA. *Boletín de la Sociedad Geológica Mexicana*, 65(1), 123-136.
- Galloway, D. L., Jones, D. R., & Ingebritsen, S. E. (Eds.). (1999). *Land subsidence in the United States* (Vol. 1182). Geological Survey (USGS).

- Gathala, M. K., Kumar, V., Sharma, P. C., Saharawat, Y. S., Jat, H. S., Singh, M., ... & Ladha, J. K. (2013). Optimizing intensive cereal-based cropping systems addressing current and future drivers of agricultural change in the northwestern Indo-Gangetic Plains of India. *Agriculture, ecosystems & environment*, 177, 85-97.
- Gonzales-Inca, C., Calle, M., Croghan, D., Torabi Haghighi, A., Marttila, H., Silander, J., & Alho, P. (2022). Geospatial artificial intelligence (GeoAI) in the integrated hydrological and fluvial systems modeling: Review of current applications and trends. *Water*, 14(14), 2211.
- Grey, D., & Sadoff, C. W. (2007). Sink or swim? Water security for growth and development. *Water policy*, 9(6), 545-571.
- Ibrahim, A., Wayayok, A., Shafri, H. Z. B. M., & Toridi, N. M. (2026). Machine-Learning Downscaling of GRACE/GRACE-FO for Basin-Scale Groundwater Storage Assessment in a Semi-Arid Basin.
- Islam, S., Gathala, M. K., Tiwari, T. P., Timsina, J., Laing, A. M., Maharjan, S., ... & Gérard, B. (2019). Conservation agriculture based sustainable intensification: Increasing yields and water productivity for smallholders of the Eastern Gangetic Plains. *Field Crops Research*, 238, 1-17.
- Jat, H. S., Datta, A., Choudhary, M., Sharma, P. C., & Jat, M. L. (2021). Conservation Agriculture: factors and drivers of adoption and scalable innovative practices in Indo-Gangetic plains of India—a review. *International Journal of Agricultural Sustainability*, 19(1), 40-55.
- Kumar, A., & Nehdi, M. L. (2026). Data-driven approaches to groundwater modelling: methods, applications, and challenges. *Hydrological Insights*, 1-10.
- Kumar, S., Park, E., Tran, D. D., Vo, T. Q., Kästner, K., Kantoush, S., ... & Switzer, A. D. (2026). Counterfactual modeling isolates sand mining impacts, revealing it as a key driver of Mekong Delta destabilization. *Science Advances*, 12(28), eaef0558.
- Kyriou, A., Mpelogianni, V., Nikolakopoulos, K., & Groumpos, P. P. (2023). Review of remote sensing approaches and soft computing for infrastructure monitoring. *Geomatics*, 3(3), 367-392.
- Leader, T., & Wijnen, M. (2018). Assessment of groundwater challenges & opportunities in support of sustainable development in Sub-Saharan Africa. *The World Bank: Washington, DC, USA*.
- Leijnse, M., FP Bierkens, M., HM Gommans, K., Lin, D., Tait, A., & Wanders, N. (2024). Key drivers and pressures of global water scarcity hotspots. *Environmental Research Letters*, 19(5), 054035.
- Li, X., Zhu, L., Zhang, W., Xiong, F., Dang, F., Liu, F., & Cao, Z. (2026). Machine Learning-Driven Multi-Scale Modeling and Digital Twin Evolution for Geothermal Reservoirs and Underground Thermal Storage. *Applied Sciences*, 16(16), 8301.
- Lu, J., Kong, D., Zhang, Y., Xie, Y., Gu, X., & Gulakhmadov, A. (2025). Hotspots of global water resource changes and their causes. *Earth's Future*, 13(2), e2024EF005461.
- Mishra, B. K., Kumar, P., Saraswat, C., Chakraborty, S., & Gautam, A. (2021). Water security in a changing environment: Concept, challenges and solutions. *Water*, 13(4), 490.
- Ojha, C., Shirzaei, M., Werth, S., Argus, D. F., & Farr, T. G. (2018). Sustained groundwater loss in California's Central Valley exacerbated by intense drought periods. *Water Resources Research*, 54(7), 4449-4460.
- Ortega-Guerrero, A., Rudolph, D. L., & Cherry, J. A. (1999). Analysis of long-term land subsidence near Mexico City: Field investigations and predictive modeling. *Water resources research*, 35(11), 3327-3341.
- Overacker, J., Hammond, W. C., Blewitt, G., & Kreemer, C. (2022). Vertical land motion of the high plains aquifer region of the united states: Effect of aquifer confinement style, climate variability, and anthropogenic activity. *Water Resources Research*, 58(6), e2021WR031635.
- Pacheco-Martínez, J., Hernandez-Marín, M., Burbey, T. J., González-Cervantes, N., Ortiz-Lozano, J. Á., Zermeño-De-Leon, M. E., & Solís-Pinto, A. (2013). Land subsidence and ground failure

- associated to groundwater exploitation in the Aguascalientes Valley, México. *Engineering Geology*, 164, 172-186.
- Pahl-Wostl, C., Palmer, M., & Richards, K. (2013). Enhancing water security for the benefits of humans and nature the role of governance. *Current Opinion in Environmental Sustainability*, 5(6), 676-684.
- Palma, A., Rivera, A., & Carmona, R. (2022). A unified hydrogeological conceptual model of the Mexico Basin aquifer after a century of groundwater exploitation. *Water*, 14(10), 1584.
- Parker, A. L., Featherstone, W. E., Penna, N. T., Filmer, M. S., & Garthwaite, M. C. (2017). Practical considerations before installing ground-based geodetic infrastructure for integrated InSAR and cGNSS monitoring of vertical land motion. *Sensors*, 17(8), 1753.
- Pierrat, E., Dorber, M., de Graaf, I., Laurent, A., Hauschild, M. Z., Rygaard, M., & Barbarossa, V. (2023). Multicompartment depletion factors for water consumption on a global scale. *Environmental science & technology*, 57(10), 4318.
- Pollard, S., Biggs, H., & Du Toit, D. R. (2014). A systemic framework for context-based decision making in natural resource management: reflections on an integrative assessment of water and livelihood security outcomes following policy reform in South Africa. *Ecology and Society*, 19(2).
- Portilho-Ramos, R. D. C., Titschack, J., Wienberg, C., Siccha Rojas, M. G., Yokoyama, Y., & Hebbeln, D. (2022). Major environmental drivers determining life and death of cold-water corals through time. *PLoS Biology*, 20(5), e3001628.
- Ramakrishnan, J., John, R., Mavaluru, D., Ravali, R. S., & Srinivasan, K. (2024). Transforming groundwater sustainability, management and development through deep learning. *Groundwater for Sustainable Development*, 27, 101366.
- Reddy, V. R., Pavelic, P., & Reddy, M. S. (2021). Participatory management and sustainable use of groundwater: a review of the Andhra Pradesh Farmer-Managed Groundwater Systems project in India.
- Saha, D., Sikka, A. K., & Goklani, R. (2022). Artificial recharge endeavours in India: a review. *Water Security*, 16, 100121.
- Samalavičius, V., Solovey, T., Śliwińska-Bronowicz, J., Stradczuk, A., & Zaslavsky, I. (2026). Bias-Aware Machine Learning Spatial Downscaling of GRACE Signals: Application to the Bug River Basin. *Remote Sensing*, 18(17), 2909.
- Scott, C. A., Meza, F. J., Varady, R. G., Tiessen, H., McEvoy, J., Garfin, G. M., ... & Montaña, E. (2013). Water security and adaptive management in the arid Americas. *Annals of the Association of American Geographers*, 103(2), 280-289.
- Sheik, A. G., Kumar, A., Sharanya, A. G., Amabati, S. R., Bux, F., & Kumari, S. (2025). Machine learning-based monitoring and design of managed aquifer rechargers for sustainable groundwater management: scope and challenges. *Environmental science and pollution research*, 32(59), 31572-31605.
- Singh, A., Yadav, S. S., Joshi, E., & Khambalkar, P. A. (2022). Sustainable groundwater management, addressing depletion through advanced technology and policy. *Environmental Reports*.
- Springer, A., De Lannoy, G., Rodell, M., Ewerdwalbesloh, Y., Gerdener, H., Khaki, M., ... & Kusche, J. (2026). A review of current best practices and future directions in assimilating GRACE/-FO terrestrial water storage data into numerical models. *Hydrology and Earth System Sciences*, 30(4), 985-1022.
- Springer, A., De Lannoy, G., Rodell, M., Ewerdwalbesloh, Y., Gerdener, H., Khaki, M., ... & Kusche, J. (2025). A Review of Current Best Practices and Future Directions in Assimilating GRACE/-FO Terrestrial Water Storage Data into Numerical Models. *EGUsphere*, 2025, 1-51.

- Sun, J., Sun, X., Song, R., Hao, R., & Li, H. (2026). A knowledge map-based review of GRACE satellite applications across multiple domains: challenges and future directions. *Acta Geophysica*, 74(2), 96.
- Sun, X., Fan, D., Hu, L., & Wang, H. (2025). Global patterns and drivers of nitrogen isotope signal in modern marine sediments. *Nature Communications*, 16(1), 11363.
- Wirl, F. (1995). Impact of regulation on demand side conservation programs. *Journal of Regulatory Economics*, 7(1), 43-62.
- Xiong, Y., Feng, W., Bai, H., Chen, W., Jiang, Z., & Zhong, M. (2025). High-resolution terrestrial water storage anomalies and components in China from GRACE/GFO via joint inversion downscaling. *Water Resources Research*, 61(7), e2024WR038996.
- Zhao, W., Su, R., Zou, P., Li, Y., Yang, B., & Zhang, B. (2026). Achieving painless energy conservation via equity-oriented efficiency nudge: evidence from electricity consumption in China. *Resources, Conservation and Recycling*, 227, 108736